NSN 5930-00-681-4247

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-681-4247

Th	rea	h	lه	nc	nth	
	ıca	u	ᆫ	ıı۷	4411	

0.375 inches single mounting facility

Overall Length:

2.750 inches

Overall Height:

1.125 inches

Overall Width:

1.312 inches

First Flat Length:

0.375 inches single actuator

Flat Height:

0.218 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.875 inches single actuator

Nonturn Device Radius:

0.438 inches at 9: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 9: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

180.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

NSN 5930-00-681-4247Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
1.0 amperes resistive load ac at sea level
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Style Designator:
Circular wafer, bushing mount
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A052b0