

View Online at <https://aerobasegroup.com/nsn/5930-00-681-4595>

Body Style:

Panel mount

Overall Length:

1.375 inches

Overall Height:

0.875 inches

Overall Width:

0.875 inches

Body Diameter:

Between 0.552 inches and 0.572 inches

Body Length:

Between 0.888 inches and 0.920 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

Between 0.370 inches and 0.377 inches

Actuator Height:

Between 0.240 inches and 0.260 inches

Actuator Color:

Red single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

2 two circuit, double make, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 3.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

UNEF

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0