

View Online at <https://aerobasegroup.com/nsn/5930-00-681-5017>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.872 inches and 0.878 inches

Body Length:

1.094 inches

Body Width:

0.406 inches

Body Height:

0.625 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.114 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.403 inches and 0.409 inches

Actuator Style:

Round

Actuator Diameter:

0.110 inches

Actuator Height:

0.094 inches

Actuator Free Position Height:

0.203 inches

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

Between 4.0 ounces and 14.0 ounces

Switch Actuating Force:

0.578 inch-ounces

Actuator Movement:

Between 0.046 pretravel inches and 0.031 overtravel inches and 0.016 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 10.000 amperes resistive ac

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0