NSN 5930-00-681-5017

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-681-5017

Body Style: Hole mounted Center To Center Distance Between Mounting Facilities Parallel To Length: Between 0.872 inches and 0.878 inches Body Length: 1.094 inches Body Width: 0.406 inches Body Height: 0.625 inches Case Material: Plastic Unthreaded Mounting Hole Diameter: 0.114 inches Center To Center Distance Between Mounting Facilities Parallel To Height:
Center To Center Distance Between Mounting Facilities Parallel To Length: Between 0.872 inches and 0.878 inches Body Length: 1.094 inches Body Width: 0.406 inches Body Height: 0.625 inches Case Material: Plastic Unthreaded Mounting Hole Diameter: 0.114 inches
Between 0.872 inches and 0.878 inches Body Length: 1.094 inches Body Width: 0.406 inches Body Height: 0.625 inches Case Material: Plastic Unthreaded Mounting Hole Diameter: 0.114 inches
Body Length: 1.094 inches Body Width: 0.406 inches Body Height: 0.625 inches Case Material: Plastic Unthreaded Mounting Hole Diameter: 0.114 inches
1.094 inches Body Width: 0.406 inches Body Height: 0.625 inches Case Material: Plastic Unthreaded Mounting Hole Diameter: 0.114 inches
Body Width: 0.406 inches Body Height: 0.625 inches Case Material: Plastic Unthreaded Mounting Hole Diameter: 0.114 inches
0.406 inches Body Height: 0.625 inches Case Material: Plastic Unthreaded Mounting Hole Diameter: 0.114 inches
Body Height: 0.625 inches Case Material: Plastic Unthreaded Mounting Hole Diameter: 0.114 inches
0.625 inches Case Material: Plastic Unthreaded Mounting Hole Diameter: 0.114 inches
Case Material: Plastic Unthreaded Mounting Hole Diameter: 0.114 inches
Plastic Unthreaded Mounting Hole Diameter: 0.114 inches
Unthreaded Mounting Hole Diameter: 0.114 inches
0.114 inches
Center To Center Distance Petween Mounting Excilities Parallel To Height
Center 10 Center Distance Between Mounting Facilities Faraner 10 neight.
Between 0.403 inches and 0.409 inches
Actuator Style:
Round
Actuator Diameter:
0.110 inches
Actuator Height:
0.094 inches
Actuator Free Position Height:
0.203 inches
Maximum Voltage Rating In Volts:
250.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
Between 4.0 ounces and 14.0 ounces
Switch Actuating Force:
0.578 inch-ounces
Actuator Movement:
Between 0.046 pretravel inches and 0.031 overtravel inches and 0.016 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 10.000 amperes resistive ac
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:

N/a

NSN 5930-00-681-5017

Sensitive Switch - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A053a0