## NSN 5930-00-681-6693

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-681-6693

Thread L	_ength:
----------	---------

0.375 inches single mounting facility

First Flat Length:

0.375 inches single actuator

Flat Height:

0.218 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.875 inches single actuator

**Individual Section Quantity:** 

3

## Switch Contact Basic Design:

Nonpile-up symmetrical

**Throw Quantity:** 

8 3rd section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

15.0 dc at sea level

## **Switch Actuator Indexing Position Quantity:**

8 single actuator

**Shaft Type:** 

Round, flatted single actuator

**Terminal Type:** 

Tab, solder lug

**Contact Switching Action:** 

Breaks before makes 3rd section rear

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

**Contact Load Current Rating:** 

2.0 amperes resistive load dc at sea level

**Special Features:** 

Twelve dummy terminal on rear of 2nd section

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5930-00-681-6693

Rotary Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0