## NSN 5930-00-681-7995

Sensitive Switch - Page 1 of 2

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/5930-00-681-7995

Hole mounted
Overall Length:
0.781 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Overall Height:
0.789 inches
Overall Width:
0.250 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Body Height:
0.359 inches
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Length:
0.575 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
0.570 inches
Actuator Roller Diameter:
0.188 inches
Actuator Roller Width:
0.109 inches
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
0.5 ounces
Switch Actuating Force:

**Actuator Movement:** 

6.0 ounces

Between 0.094 pretravel inches and 0.047 overtravel inches and 0.031 differential inches

## NSN 5930-00-681-7995

Sensitive Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life: N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0