# NSN 5930-00-682-0350

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-682-0350

# Thread Length:

0.469 inches single mounting facility

# **Hazardous Locations/environmental Protection:**

Dustproof

# First Flat Length:

0.438 inches single actuator

#### Flat Height:

0.188 inches single actuator

#### **Shaft Diameter:**

0.250 inches single actuator

#### **Shaft Length:**

0.816 inches single actuator

#### **Individual Section Quantity:**

2

#### **Switch Contact Basic Design:**

Nonpile-up symmetrical

#### **Pole Quantity:**

1 each section rear

# **Throw Quantity:**

4 each section rear

# **Mounting Method:**

Threaded bushing single mounting facility

# Thready Qty Per Inch (tpi):

32 single mounting facility

#### **Thread Size:**

0.469 inches single mounting facility

# **Contact Voltage Rating In Volts:**

125.0 dc at sea level

#### **Switch Actuator Indexing Position Quantity:**

8 single actuator

# Shaft Type:

Round, flatted single actuator

# **Terminal Type:**

Tab w/screw

# **Contact Switching Action:**

Breaks before makes each section rear

# **Switch Actuator Positioning Increment:**

45.0 degrees single actuator

# **Contact Load Current Rating:**

5.0 amperes resistive load dc at sea level

# **Thread Series Designator:**

Uns single mounting facility

# NSN 5930-00-682-0350

Rotary Switch - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0