

View Online at <https://aerobasegroup.com/nsn/5930-00-682-0370>

Thread Class:

2a single mounting facility

Thread Length:

0.380 inches single mounting facility

Overall Length:

6.150 inches

Overall Height:

2.310 inches

Overall Width:

1.970 inches

First Flat Length:

0.500 inches single actuator

Flat Height:

0.218 inches single actuator

Shaft Diameter:

0.250 inches single actuator and 0.252 inches single actuator

Shaft Length:

0.560 inches single actuator

Nonturn Device Radius:

0.530 inches at 12: 00 o'clock

Individual Section Quantity:

6

Nonturn Device Type:

Tab at 12: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 1st section front1 3rd section rear1 4th section rear1 5th section rear

Throw Quantity:

11 1st section front11 3rd section rear11 4th section rear11 5th section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

11 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes 1st section frontbreaks before makes 3rd section rearbreaks before makes 4th section rearbreaks before makes 5th section rear

Switch Actuator Positioning Increment:

20.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level2.0 amperes resistive load dc at sea level

Precious Material And Location:

Contacts and totor blades silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0