

View Online at <https://aerobasegroup.com/nsn/5930-00-682-0449>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.782 inches

Body Diameter:

Between 0.245 inches and 0.250 inches

Body Length:

2.063 inches

Overall Diameter:

0.625 inches

Unthreaded Mounting Hole Diameter:

0.156 inches

Bulb Length:

2.344 inches

Bulb Diameter:

Between 0.245 inches and 0.250 inches

Temperature Sensing Element Type:

Bulb

Mounting Facility Circle Radius:

0.625 inches

Operating Temperature Rating:

Between -40.0 degrees fahrenheit and 392.0 degrees fahrenheit

Mounting Method:

Flange and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Three position circular

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Wire lead

Contact Load Current Rating:

1.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

94.00 actuation point degrees celsius and 106.00 actuation point degrees celsius and 94.00 deactuation point degrees celsius and 106.00 deactuation point degrees celsius

Contact Voltage Rating In Volts:

32.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas

Precious Material And Location:

Terminal surfaces silver

Precious Material:

Silver

Style Designator:

Cylindrical w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0