

View Online at <https://aerobasegroup.com/nsn/5930-00-683-2821>

Thread Class:

2a single mounting facility

Thread Length:

0.370 inches single mounting facility

Overall Length:

3.240 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.560 inches single actuator

Overall Diameter:

1.370 inches

Nonturn Device Radius:

0.530 inches at 3: 00 o'clock

Individual Section Quantity:

6

Nonturn Device Type:

Tab at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

5 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Precious Material And Location:

Contacts and rotors silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0