NSN 5930-00-683-4954

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-683-4954

| · | | | |
|---|--|--|--|
| Body Style: | | | |
| Bushing mounted | | | |
| Hazardous Locations/environmental Protection: | | | |
| Corrosion resistant | | | |
| Overall Length: | | | |
| 1.183 inches | | | |
| Overall Height: | | | |
| 3.650 inches | | | |
| Overall Width: | | | |
| 0.780 inches | | | |
| Bushing Length: | | | |
| 0.350 inches | | | |
| Body Length: | | | |
| 1.183 inches | | | |
| Body Width: | | | |
| 0.780 inches | | | |
| Body Height: | | | |
| 2.622 inches | | | |
| Case Material: | | | |
| Metal | | | |
| Actuator Diameter: | | | |
| 0.750 inches | | | |
| Actuator Height: | | | |
| 0.500 inches | | | |
| Actuator Color: | | | |
| Natural single actuator | | | |
| Illuminated Actuator Color: | | | |
| Natural single actuator | | | |
| Maximum Voltage Rating In Volts: | | | |
| 250.0 ac and 28.0 dc | | | |
| Inclosure Type: | | | |
| Fully enclosed | | | |
| Mounting Method: | | | |
| Threaded bushing | | | |
| Features Provided: | | | |
| Holding solenoid | | | |
| Thready Qty Per Inch (tpi): | | | |
| 24 | | | |
| Thread Size: | | | |
| 0.625 inches | | | |
| Namila un Cantact Arrangement. | | | |

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

NSN 5930-00-683-4954

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 4.000 amperes motor dc and 5.000 amperes resistive ac

| Thread | Series | Designa | tor: |
|--------|--------|---------|------|
| | | | |

Unef

Terminal Type And Quantity:

16 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0