NSN 5930-00-683-4967

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-683-4967

Thread Class:

2b single mounting facility

Overall Length:

Between 4.609 inches and 4.641 inches

Shaft Diameter:

0.248 inches single actuator and 0.252 inches single actuator

Shaft Length:

1.109 inches single actuator and 1.141 inches single actuator

Overall Diameter:

Between 2.484 inches and 2.516 inches

Unthreaded Mounting Hole Diameter:

0.238 inches single mounting facility

Individual Section Quantity:

5

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

3 each section front

Mounting Facility Circle Radius:

2.312 inches single mounting facility

Mounting Method:

Unthreaded hole single mounting facility and threaded hole single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Four position circular single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, fluted, threaded hole single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

NSN 5930-00-683-4967

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

10.0 amperes resistive load ac at sea level

Style Designator:

Circular wafer, panel mount

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0