

View Online at <https://aerobasegroup.com/nsn/5930-00-683-5977>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Moisture resistant

Actuator Style:

Adjustable arm

Actuator Diameter:

0.190 inches

Actuator Height:

1.240 inches

Actuator Width:

2.500 inches

Housing Diameter:

1.030 inches

Housing Length:

1.050 inches

Housing Bushing Length:

0.340 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Actuating Force:

48.0 inch-ounces

Actuator Movement:

12.0 differential degrees and 35.0 pretravel degrees

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 4.000 amperes motor dc

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 wire lead

Specification Data:

81349-mil-s-8805/49 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0