

View Online at <https://aerobasegroup.com/nsn/5930-00-683-6505>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.684 inches and 0.690 inches

Body Length:

Between 1.790 inches and 1.810 inches

Body Width:

0.812 inches

Body Height:

Between 0.825 inches and 0.855 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.140 inches

Actuator Style:

Round

Actuator Diameter:

0.305 inches

Actuator Height:

0.213 inches

Actuator Free Position Height:

0.867 inches

Maximum Voltage Rating In Volts:

600.0 ac and 220.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 9.0 ounces and 15.0 ounces

Contact Load Current Rating At Maximum Rated Voltage:

0.200 amperes resistive dc and 5.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0