NSN 5930-00-683-6505

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-683-6505					
Body Style:					
Hole mounted					
Hazardous Locations/environmental Protection:					
Dustproof					
Center To Center Distance Between Mounting Facilities Parallel To Length:					
Between 0.684 inches and 0.690 inches					
Body Length:					
Between 1.790 inches and 1.810 inches					
Body Width:					
0.812 inches					
Body Height:					
Between 0.825 inches and 0.855 inches					
Case Material:					
Plastic					
Unthreaded Mounting Hole Diameter:					
0.140 inches					
Actuator Style:					
Round					
Actuator Diameter:					
0.305 inches					
Actuator Height:					
0.213 inches					
Actuator Free Position Height:					
0.867 inches					
Maximum Voltage Rating In Volts:					
600.0 ac and 220.0 dc					
Inclosure Type:					
Fully enclosed					
Mounting Method:					
Unthreaded hole					
Nonpile-up Contact Arrangement:					
1 two circuit, double break/double make, one position momentary single switch unit					
Switch Release Force:					
4.0 ounces					
Switch Actuating Force:					
Between 9.0 ounces and 15.0 ounces					
Contact Load Current Rating At Maximum Rated Voltage:					

0.200 amperes resistive dc and 5.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

4 screw

NSN 5930-00-683-6505

Sensitive Switch - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0