NSN 5930-00-683-6522

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-683-6522

Body Style:

Hole mounted

Overall Length:

1.156 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

Overall Height:

0.531 inches

Overall Width:

0.250 inches

Body Length:

0.781 inches

Body Width:

0.250 inches

Body Height:

0.438 inches

Unthreaded Mounting Hole Diameter:

0.088 inches

Actuator Length:

0.125 inches

Actuator Style:

Rectangular

Actuator Height:

0.093 inches

Actuator Width:

0.125 inches

Actuator Free Position Height:

0.406 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 two circuit, one position momentary single switch unit

Switch Release Force:

2.0 ounces

Switch Actuating Force:

4.5 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.012 overtravel inches and 0.020 differential inches

NSN 5930-00-683-6522

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes inductive dc and 10.000 amperes resistive ac

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0