

View Online at <https://aerobasegroup.com/nsn/5930-00-685-9796>

**Inside Diameter:**

0.500 inches single connection

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

3.844 inches

**Overall Height:**

3.500 inches

**Body Diameter:**

3.750 inches

**Unthreaded Mounting Hole Diameter:**

0.203 inches

**Distance Between Mounting Facility Centers:**

2.250 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and unthreaded hole

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

160.00 pounds per square inch

**Thread Size:**

0.500 inches single pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

5.0 amperes resistive load second voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+3.30/+80.00 actuation point pounds per square inch and +0.50/+77.20 deactuation point pounds per square inch

**Contact Adjustment Type:**

External deactuation point hex nut and external actuation point hex nut

**Contact Voltage Rating In Volts:**

250.0 dc at sea level second voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Frequency In Hertz:**

60.0 first voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical w/bracket

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0