

View Online at <https://aerobasegroup.com/nsn/5930-00-685-9796>

Inside Diameter:

0.500 inches single connection

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

3.844 inches

Overall Height:

3.500 inches

Body Diameter:

3.750 inches

Unthreaded Mounting Hole Diameter:

0.203 inches

Distance Between Mounting Facility Centers:

2.250 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

160.00 pounds per square inch

Thread Size:

0.500 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

5.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+3.30/+80.00 actuation point pounds per square inch and +0.50/+77.20 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point hex nut and external actuation point hex nut

Contact Voltage Rating In Volts:

250.0 dc at sea level second voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/bracket

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0