

View Online at <https://aerobasegroup.com/nsn/5930-00-686-0105>

**Body Style:**

Bushing mounted

**Overall Length:**

Between 1.234 inches and 1.266 inches

**Overall Height:**

Between 3.603 inches and 3.792 inches

**Overall Width:**

0.812 inches

**Bushing Length:**

Between 0.484 inches and 0.516 inches

**Body Length:**

Between 1.922 inches and 1.963 inches

**Body Width:**

0.656 inches

**Body Height:**

Between 1.234 inches and 1.266 inches

**Actuator Style:**

Round

**Actuator Height:**

Between 0.828 inches and 0.922 inches

**Actuator Position-action Relationship:**

Up position maintained and center position maintained

**Actuator Position-locking Relationship:**

Up position no locking action and center position locked in and out

**Maximum Voltage Rating In Volts:**

125.0 ac

**Inclosure Type:**

Uninclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

20

**Pile-up Contact Form Arrangement:**

2a1b single position

**Thread Size:**

0.500 inches

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive ac

**Precious Material And Location:**

Contacts silver

**Thread Series Designator:**

Unf

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0