# NSN 5930-00-686-1588

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-686-1588

## Thread Class:

2b single mounting facility

#### Thread Length:

0.469 inches single mounting facility

## Hazardous Locations/environmental Protection:

Dustproof

#### **Overall Length:**

2.750 inches

#### Shaft Diameter:

0.247 inches single actuator

#### Shaft Length:

0.938 inches single actuator

#### **Overall Diameter:**

1.875 inches

#### Individual Section Quantity:

3

## Nonturn Device Type:

Slotted bushing at 12: 00 o'clock

## Switch Contact Basic Design:

Nonpile-up nonsymmetrical

#### Mounting Method:

Threaded bushing single mounting facility

#### Thready Qty Per Inch (tpi):

32 single mounting facility

#### Thread Size:

0.469 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

125.0 ac at sea level

## Switch Actuator Indexing Position Quantity:

8 single actuator

#### Shaft Type:

Round single actuator

#### **Terminal Type:**

Screw

#### Contact Switching Action:

Makes before breaks 2nd section front

#### Switch Actuator Positioning Increment:

45.0 degrees single actuator

## Switch Actuator Stop Device Type:

Fixed stop single actuator

#### **Contact Load Current Rating:**

5.0 amperes resistive load ac at sea level

# NSN 5930-00-686-1588

Rotary Switch - Page 2 of 2

## Style Designator:

Tap, circular, bushing mount

## Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A052b0

