NSN 5930-00-686-2940

Sensitive Switch - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5930-00-686-2940

Hole mounted
Overall Length:
0.781 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Overall Height:
0.750 inches
Overall Width:
0.250 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Body Height:
0.359 inches
Unthreaded Mounting Hole Diameter:
0.096 inches
Actuator Length:
0.296 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
0.562 inches
Actuator Roller Diameter:
0.187 inches
Actuator Roller Width:
0.109 inches
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
1.0 ounces

Actuator Movement:

10.0 ounces

Switch Actuating Force:

Between 0.031 pretravel inches and 0.010 overtravel inches and 0.003 differential inches

NSN 5930-00-686-2940

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.500 amperes inductive dc

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0