NSN 5930-00-686-2940

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-686-2940

Hole mounted

Overall Length:

0.781 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Overall Height:

0.750 inches

Overall Width:

0.250 inches

Body Length:

0.781 inches

Body Width:

0.250 inches

Body Height:

0.359 inches

Unthreaded Mounting Hole Diameter:

0.096 inches

Actuator Length:

0.296 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

0.562 inches

Actuator Roller Diameter:

0.187 inches

Actuator Roller Width:

0.109 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

10.0 ounces

Actuator Movement:

Between 0.031 pretravel inches and 0.010 overtravel inches and 0.003 differential inches

NSN 5930-00-686-2940

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.500 amperes inductive dc

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0