## NSN 5930-00-687-0952

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-687-0952

Hazardous Locations/environmental Protection:
Watertight
Overall Length:
5.594 inches
Overall Height:
2.688 inches
Overall Width:
5.000 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Shortest Horizontal Distance Between Mounting Centers:
0.656 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Increase
Thread Size:
0.250 inches single pressure connection
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Tab w/screw
Tab w/screw  Contact Load Current Rating:
Contact Load Current Rating:
Contact Load Current Rating: 3.4 amperes resistive load single voltage
Contact Load Current Rating:  3.4 amperes resistive load single voltage  Contact Adjustability:
Contact Load Current Rating:  3.4 amperes resistive load single voltage  Contact Adjustability:  Deactuation point not adjustable and actuation point adjustable, preset
Contact Load Current Rating:  3.4 amperes resistive load single voltage  Contact Adjustability:  Deactuation point not adjustable and actuation point adjustable, preset  Contact Adjustment Range:
Contact Load Current Rating:  3.4 amperes resistive load single voltage  Contact Adjustability:  Deactuation point not adjustable and actuation point adjustable, preset  Contact Adjustment Range:  +5.00/+75.00 actuation point pounds per square inch
Contact Load Current Rating:  3.4 amperes resistive load single voltage  Contact Adjustability:  Deactuation point not adjustable and actuation point adjustable, preset  Contact Adjustment Range:  +5.00/+75.00 actuation point pounds per square inch  Contact Adjustment Type:
Contact Load Current Rating:  3.4 amperes resistive load single voltage  Contact Adjustability:  Deactuation point not adjustable and actuation point adjustable, preset  Contact Adjustment Range:  +5.00/+75.00 actuation point pounds per square inch  Contact Adjustment Type:  External actuation point screw
Contact Load Current Rating:  3.4 amperes resistive load single voltage  Contact Adjustability:  Deactuation point not adjustable and actuation point adjustable, preset  Contact Adjustment Range: +5.00/+75.00 actuation point pounds per square inch  Contact Adjustment Type:  External actuation point screw  Contact Voltage Rating In Volts:

Thread Series Designator:

Npt single pressure connection

## NSN 5930-00-687-0952

Pressure Switch - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0