## NSN 5930-00-687-1903

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-687-1903

**Thread Class:** 

2a single mounting facility

Thread Length:

0.219 inches single mounting facility

**Overall Length:** 

2.000 inches

**Overall Height:** 

Between 1.022 inches and 1.042 inches

**Overall Width:** 

0.938 inches

First Flat Length:

0.281 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.531 inches single actuator

**Nonturn Device Radius:** 

0.375 inches at 3: 00 o'clock

**Individual Section Quantity:** 

2

**Nonturn Device Type:** 

Tab at 3: 00 o'clock

End Application:

Aircraft, hercules c-130f, aircraft, starlifter c-141.

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

2 each section rear

**Throw Quantity:** 

2 each section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

110.0 ac at sea level

**Switch Actuator Indexing Position Quantity:** 

2 single actuator

**Shaft Type:** 

Round, v flatted single actuator

**Criticality Code Justification:** 

Feat

## NSN 5930-00-687-1903

Rotary Switch - Page 2 of 2



Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
60.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
150.0 milliamperes resistive load ac at sea level
Special Features:
Weapon system essential
Style Designator:
Circular wafer, bushing mount
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A052b0