NSN 5930-00-687-1903

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-687-1903

Thread Class:

2a single mounting facility

Thread Length:

0.219 inches single mounting facility

Overall Length:

2.000 inches

Overall Height:

Between 1.022 inches and 1.042 inches

Overall Width:

0.938 inches

First Flat Length:

0.281 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.531 inches single actuator

Nonturn Device Radius:

0.375 inches at 3: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 3: 00 o'clock

End Application:

Aircraft, hercules c-130f, aircraft, starlifter c-141.

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

2 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

110.0 ac at sea level

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, v flatted single actuator

Criticality Code Justification:

Feat

NSN 5930-00-687-1903

Rotary Switch - Page 2 of 2



Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
60.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
150.0 milliamperes resistive load ac at sea level
Special Features:
Weapon system essential
Style Designator:
Circular wafer, bushing mount
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A052b0