NSN 5930-00-687-1931

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-687-1931

| Maximum Voltage Rating In Volts: |
|--|
| 460.0 ac and 250.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.469 inches |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary single switch unit |
| Switch Release Force: |
| 4.0 ounces |
| Switch Actuating Force: |
| 13.0 ounces |
| Actuator Movement: |
| Between 0.015 pretravel inches and 0.140 overtravel inches and 0.001 differential inches |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 250.000 milliamperes resistive dc and 15.000 amperes resistive ac |
| Special Features: |
| Plunger w/roller rotated 90 degrees to side |
| Thread Series Designator: |
| Uns |
| Terminal Type And Quantity: |
| 3 screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A053a0 |
| |
| |