# NSN 5930-00-687-2056

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-687-2056

# Thread Length:

0.250 inches single mounting facility

## **Hazardous Locations/environmental Protection:**

Dustproof and watertight

## First Flat Length:

0.250 inches single actuator

#### Flat Height:

0.220 inches single actuator

#### **Shaft Diameter:**

0.250 inches single actuator

#### **Shaft Length:**

0.560 inches single actuator

#### **Individual Section Quantity:**

2

#### **Switch Contact Basic Design:**

Nonpile-up symmetrical

#### **Pole Quantity:**

1 each section front

## **Throw Quantity:**

3 each section rear

# **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

# **Contact Voltage Rating In Volts:**

115.0 ac at sea level

# **Switch Actuator Indexing Position Quantity:**

10 single actuator

#### **Shaft Type:**

Round, flatted single actuator

# **Terminal Type:**

Tab, solder lug

# **Contact Switching Action:**

Makes before breaks each section rear

# **Switch Actuator Positioning Increment:**

36.0 degrees single actuator

# **Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

# **Thread Series Designator:**

Unef single mounting facility

#### Shelf Life:

N/a

# **NSN 5930-00-687-2056**Rotary Switch - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

Demilitarization:

No

Fiig:

A052b0