

View Online at <https://aerobasegroup.com/nsn/5930-00-687-2281>

Thread Class:

2a

Body Style:

Bushing/hole mounted

Overall Length:

0.825 inches

Overall Height:

1.410 inches

Overall Width:

0.375 inches

Bushing Length:

0.350 inches

Body Length:

0.825 inches

Body Width:

0.375 inches

Body Height:

0.505 inches

Case Material:

Plastic

Actuator Style:

Roller plunger

Actuator Free Position Height:

0.781 inches

Actuator Roller Diameter:

0.250 inches

Actuator Roller Width:

0.060 inches

Maximum Voltage Rating In Volts:

30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

10.0 ounces

Actuator Movement:

Between 0.035 pretravel inches and 0.030 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes inductive dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0