## NSN 5930-00-687-2281

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-687-2281 **Thread Class:** 2a **Body Style:** Bushing/hole mounted **Overall Length:** 0.825 inches **Overall Height:** 1.410 inches **Overall Width:** 0.375 inches **Bushing Length:** 0.350 inches **Body Length:** 0.825 inches **Body Width:** 0.375 inches **Body Height:** 0.505 inches **Case Material:** Plastic **Actuator Style:** Roller plunger **Actuator Free Position Height:** 0.781 inches **Actuator Roller Diameter:** 0.250 inches **Actuator Roller Width:** 0.060 inches **Maximum Voltage Rating In Volts:** 30.0 dc Inclosure Type: Fully enclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 40 **Thread Size:** 0.250 inches **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit

**Switch Release Force:** 

4.0 ounces

## **NSN 5930-00-687-2281** Sensitive Switch - Page 2 of 2



Switch Actuating Force:
10.0 ounces
Actuator Movement:
Between 0.035 pretravel inches and 0.030 overtravel inches and 0.005 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
1.000 amperes inductive dc
Thread Series Designator:
Uns
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A053a0