

View Online at <https://aerobasegroup.com/nsn/5930-00-687-2282>

Thread Class:

3b single pressure connection

Inside Diameter:

0.438 inches single connection

Overall Length:

4.250 inches

Overall Height:

3.563 inches

Overall Width:

4.063 inches

Body Diameter:

3.000 inches

Mounting Slot Width:

Between 0.195 inches and 0.200 inches

Body Length:

2.688 inches

Unthreaded Mounting Hole Diameter:

Between 0.195 inches and 0.200 inches

Longest Horizontal Distance Between Mounting Centers:

0.625 inches

Longest Vertical Distance Between Mounting Centers:

3.000 inches

Pressure Switch Type:

Gage

Mounting Method:

Flange and slot and unthreaded hole

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

500.0 milliamperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+15.00/+35.00 actuation point pounds per square inch and +15.00/+35.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point shaft and external actuation point shaft

Contact Voltage Rating In Volts:

30.0 dc at sea level single voltage

Pressure Connector Type:

Double compression, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/mounting lugs

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0