NSN 5930-00-687-2282

Pressure Switch - Page 1 of 2



| - |
|---|
| View Online at https://aerobasegroup.com/nsn/5930-00-687-2282 |
| Thread Class: |
| 3b single pressure connection |
| Inside Diameter: |
| 0.438 inches single connection |
| Overall Length: |
| 4.250 inches |
| Overall Height: |
| 3.563 inches |
| Overall Width: |
| 4.063 inches |
| Body Diameter: |
| 3.000 inches |
| Mounting Slot Width: |
| Between 0.195 inches and 0.200 inches |
| Body Length: |
| 2.688 inches |
| Unthreaded Mounting Hole Diameter: |
| Between 0.195 inches and 0.200 inches |
| Longest Horizontal Distance Between Mounting Centers: |
| 0.625 inches |
| Longest Vertical Distance Between Mounting Centers: |
| 3.000 inches |
| Pressure Switch Type: |
| Gage |
| Mounting Method: |
| Flange and slot and unthreaded hole |
| Thready Qty Per Inch (tpi): |
| 20 single pressure connection |
| Contact Action Stimulus: |
| Increase |
| Thread Size: |
| 0.438 inches single pressure connection |
| |

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

500.0 milliamperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

NSN 5930-00-687-2282

Pressure Switch - Page 2 of 2



Contact Adjustment Range:

+15.00/+35.00 actuation point pounds per square inch and +15.00/+35.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point shaft and external actuation point shaft

Contact Voltage Rating In Volts:

30.0 dc at sea level single voltage

Pressure Connector Type:

Double compression, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/mounting lugs

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0