NSN 5930-00-688-4031

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-688-4031

Double compression, threaded internal all connections

Thread Class:
3a all pressure connection
Overall Length:
4.375 inches
Overall Height:
3.500 inches
Overall Width:
3.625 inches
Body Diameter:
3.000 inches
Unthreaded Mounting Hole Diameter:
0.203 inches
Distance Between Mounting Facility Centers:
3.000 inches
Pressure Switch Type:
Gage
Mounting Method:
Flange and unthreaded hole
Thready Qty Per Inch (tpi):
20 all pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
100.00 pounds per square inch gage
Thread Size:
0.438 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
1.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
56.20 actuation point inches of water and 29.50 deactuation point inches of water and 26.70 differential point inches of water
Contact Voltage Rating In Volts:
30.0 dc at sea level single voltage
Pressure Connector Type:

NSN 5930-00-688-4031Pressure Switch - Page 2 of 2



Media For Which Designed:
Gas or liquid
Style Designator:
Cylindrical w/mounting lugs
Thread Series Designator:
Unf all pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0