NSN 5930-00-688-4144

Sensitive Switch - Page 1 of 2

Body Style:Hole mounted

3 tab, solder lug



View Online at https://aerobasegroup.com/nsn/5930-00-688-4144

Overall Length:
0.781 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Overall Height:
0.528 inches
Overall Width:
0.250 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Body Height:
0.360 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Style:
Leaf
Actuator Width:
0.125 inches
Actuator Free Position Height:
0.340 inches
Maximum Voltage Rating In Volts:
30.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
0.5 ounces
Switch Actuating Force:
4.0 ounces
Actuator Movement:
Between 0.620 pretravel inches and 0.310 overtravel inches and 0.020 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc
Terminal Type And Quantity:

NSN 5930-00-688-4144

Sensitive Switch - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0