## NSN 5930-00-688-9823

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-688-9823

Overall Height:
10.562 inches
Overall Width:
3.500 inches
Body Height:
7.875 inches
Unthreaded Mounting Hole Diameter:
0.250 inches
Capillary Tube Length:
72.0 inches
Bulb Length:
3.000 inches
Bulb Diameter:
0.375 inches
Longest Horizontal Distance Between Mounting Centers:
7.250 inches
Shortest Horizontal Distance Between Mounting Centers:
2.750 inches
Longest Vertical Distance Between Mounting Centers:
4.656 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Cupinary tube builb
Mounting Method:
Mounting Method:
Mounting Method: Bracket and unthreaded hole
Mounting Method: Bracket and unthreaded hole Features Provided:
Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port
Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus:
Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus: Increase
Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus: Increase Mounting Facility Pattern:
Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle
Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle Nonpile-up Contact Arrangement:
Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary
Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type:
Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw
Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating:
Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 500.0 milliamperes resistive load third voltage
Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 500.0 milliamperes resistive load third voltage Contact Adjustability:
Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Screw Contact Load Current Rating: 500.0 milliamperes resistive load third voltage Contact Adjustability: Deactuation point adjustable and actuation point adjustable

Contact Adjustillent Type

External deactuation point knob with scale and external actuation point knob with scale

## NSN 5930-00-688-9823

Thermostatic Switch - Page 2 of 2



Contact	Voltage Ra	ting in '	Volts:
250.0 dc	at sea level	second	voltage

**Media For Which Designed:** 

Gas or liquid

**Style Designator:** 

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0