

View Online at <https://aerobasegroup.com/nsn/5930-00-688-9823>

**Overall Height:**

10.562 inches

**Overall Width:**

3.500 inches

**Body Height:**

7.875 inches

**Unthreaded Mounting Hole Diameter:**

0.250 inches

**Capillary Tube Length:**

72.0 inches

**Bulb Length:**

3.000 inches

**Bulb Diameter:**

0.375 inches

**Longest Horizontal Distance Between Mounting Centers:**

7.250 inches

**Shortest Horizontal Distance Between Mounting Centers:**

2.750 inches

**Longest Vertical Distance Between Mounting Centers:**

4.656 inches

**Temperature Sensing Element Type:**

Capillary tube-bulb

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Electrical access port

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Isosceles triangle

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

500.0 milliamperes resistive load third voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+100.00/+700.00 actuation point degrees fahrenheit and +100.00/+700.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

External deactuation point knob with scale and external actuation point knob with scale

**Contact Voltage Rating In Volts:**

250.0 dc at sea level second voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A048b0