

View Online at <https://aerobasegroup.com/nsn/5930-00-688-9823>

Overall Height:

10.562 inches

Overall Width:

3.500 inches

Body Height:

7.875 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Capillary Tube Length:

72.0 inches

Bulb Length:

3.000 inches

Bulb Diameter:

0.375 inches

Longest Horizontal Distance Between Mounting Centers:

7.250 inches

Shortest Horizontal Distance Between Mounting Centers:

2.750 inches

Longest Vertical Distance Between Mounting Centers:

4.656 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

500.0 milliamperes resistive load third voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+100.00/+700.00 actuation point degrees fahrenheit and +100.00/+700.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point knob with scale and external actuation point knob with scale

Contact Voltage Rating In Volts:

250.0 dc at sea level second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A048b0