

View Online at <https://aerobasegroup.com/nsn/5930-00-689-1235>

**Body Style:**

Bushing mount

**Bushing Length:**

Between 0.439 inches and 0.501 inches

**Body Length:**

1.400 inches

**Body Width:**

1.000 inches

**Body Height:**

1.200 inches

**Actuator Style:**

Round

**Actuator Height:**

Between 0.659 inches and 0.721 inches

**Actuator Position-action Relationship:**

Up position momentary and up position maintained

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 5.000 amperes inductive dc and 2.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 2.000 amperes lamp ac

**Test Data Document:**

81349-mil-s-81551 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

**Demilitarization:**

No

**Fig:**

A053a0