

View Online at <https://aerobasegroup.com/nsn/5930-00-689-1235>

Body Style:

Bushing mount

Bushing Length:

Between 0.439 inches and 0.501 inches

Body Length:

1.400 inches

Body Width:

1.000 inches

Body Height:

1.200 inches

Actuator Style:

Round

Actuator Height:

Between 0.659 inches and 0.721 inches

Actuator Position-action Relationship:

Up position momentary and up position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 2.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 2.000 amperes lamp ac

Test Data Document:

81349-mil-s-81551 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0