NSN 5930-00-689-1459

Sensitive Switch - Page 1 of 2

Thread Class:

Body Style:Hole mounted

1.000 inchesBody Length:1.940 inchesBody Width:

2b



View Online at https://aerobasegroup.com/nsn/5930-00-689-1459

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.687 inches
Body Height:
0.950 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.169 inches
Actuator Style:
Round
Actuator Diameter:
0.094 inches
Actuator Free Position Height:
1.030 inches
Maximum Voltage Rating In Volts:
480.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded hole
Threaded hole Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 32
Thready Qty Per Inch (tpi): 32 Thread Size:
Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches
Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement:
Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 1 pole, double throw, two positions momentary single switch unit
Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 1 pole, double throw, two positions momentary single switch unit Switch Release Force:
Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 1 pole, double throw, two positions momentary single switch unit Switch Release Force: 10.0 ounces
Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 1 pole, double throw, two positions momentary single switch unit Switch Release Force: 10.0 ounces Switch Actuating Force:
Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 1 pole, double throw, two positions momentary single switch unit Switch Release Force: 10.0 ounces Switch Actuating Force: Between 14.0 ounces and 22.0 ounces
Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 1 pole, double throw, two positions momentary single switch unit Switch Release Force: 10.0 ounces Switch Actuating Force: Between 14.0 ounces and 22.0 ounces Actuator Movement:
Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 1 pole, double throw, two positions momentary single switch unit Switch Release Force: 10.0 ounces Switch Actuating Force: Between 14.0 ounces and 22.0 ounces Actuator Movement: Between 0.050 pretravel inches and 0.094 overtravel inches and 0.002 differential inches
Thready Qty Per Inch (tpi): 32 Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 1 pole, double throw, two positions momentary single switch unit Switch Release Force: 10.0 ounces Switch Actuating Force: Between 14.0 ounces and 22.0 ounces Actuator Movement: Between 0.050 pretravel inches and 0.094 overtravel inches and 0.002 differential inches Contact Load Current Rating At Maximum Rated Voltage:

NSN 5930-00-689-1459 Sensitive Switch - Page 2 of 2



Thread Series Designator:
Unc
Terminal Type And Quantity:
3 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0