NSN 5930-00-689-1898

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-689-1898

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Industrial use

Housing Height:

3.188 inches

Housing Length:

4.938 inches

Housing Width:

2.281 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.625 inches

Maximum Voltage Rating In Volts:

600.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

20

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Switch Actuating Force:

240.0 inch-ounces

Actuator Movement:

18.0 pretravel degrees and 72.0 overtravel degrees and 14.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

750.000 milliamperes resistive dc and 2.500 amperes resistive ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0