## NSN 5930-00-689-1969

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-689-1969

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Industrial use
Overall Length:
7.078 inches
Overall Height:
2.063 inches
Overall Width:
2.313 inches
Actuator Length:
2.125 inches
Actuator Style:
Roller arm
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.250 inches
Housing Height:
2.063 inches
Housing Length:
4.953 inches
Housing Width:
2.313 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
4.219 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.813 inches
Maximum Voltage Rating In Volts:
600.0 ac and 600.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
2 pole, single throw, normally open, double make, momentary action single switch unit
Switch Actuating Force:
150.0 inch-ounces
Actuator Movement:
35.0 pretravel degrees and 45.0 overtravel degrees and 11.0 differential degrees
Contact Load Current Rating At Maximum Rated Voltage:

Terminal Type And Quantity:

200.000 milliamperes resistive dc and 1.200 amperes resistive ac

4 screw

## NSN 5930-00-689-1969

Sensitive Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0