# NSN 5930-00-689-4597

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-689-4597

# **Thread Class:**

2a single mounting facility

## Thread Length:

0.375 inches single mounting facility

# **Overall Length:**

1.451 inches

## **Overall Height:**

1.000 inches

#### **Overall Width:**

0.937 inches

#### Shaft Diameter:

0.250 inches single actuator

## Shaft Length:

0.375 inches single actuator

#### **Nonturn Device Radius:**

# 0.375 inches at 3: 00 o'clock

## Individual Section Quantity:

1

#### Nonturn Device Type:

Tab at 3: 00 o'clock

## Switch Contact Basic Design:

Nonpile-up nonsymmetrical

## **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

## **Contact Voltage Rating In Volts:**

28.0 dc at sea level

## Switch Actuator Indexing Position Quantity:

5 single actuator

#### Shaft Type:

Round single actuator

## **Terminal Type:**

Clip

# Contact Switching Action:

Breaks before makes single section rear

# Switch Actuator Positioning Increment:

30.0 degrees single actuator

# Detent Rotational Torque Range:

+10.000/+25.000 inch-ounces single actuator

# Switch Actuator Stop Device Type:

Fixed stop single actuator

# NSN 5930-00-689-4597

Rotary Switch - Page 2 of 2



**Contact Load Current Rating:** 

1.0 amperes resistive load ac at sea level

#### Precious Material And Location:

Clips and rotor blades silver

**Precious Material:** 

Silver

Style Designator:

Circular wafer, bushing mount

# **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A052b0