NSN 5930-00-689-4814

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-689-4814

| Body Style: |
|--|
| Hole mounted |
| Hazardous Locations/environmental Protection: |
| Dustproof |
| Overall Length: |
| 1.109 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.875 inches |
| Overall Width: |
| 0.400 inches |
| Body Length: |
| 1.109 inches |
| Body Width: |
| 0.400 inches |
| Body Height: |
| 0.641 inches |
| Case Material: |
| Plastic |
| Unthreaded Mounting Hole Diameter: |
| 0.126 inches |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.165 inches |
| Maximum Voltage Rating In Volts: |
| 250.0 ac and 250.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Unthreaded hole |
| Features Provided: |
| Actuator seal |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally closed, momentary action single switch unit |
| Switch Release Force: |
| 4.0 ounces |
| Switch Actuating Force: |
| 14.0 ounces |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 250.000 milliamperes resistive dc and 15.000 amperes resistive ac |

2 tab, solder lug

Terminal Type And Quantity:

NSN 5930-00-689-4814

Sensitive Switch - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0