

View Online at <https://aerobasegroup.com/nsn/5930-00-690-3466>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

Between 1.295 inches and 1.325 inches

**Overall Width:**

Between 0.735 inches and 0.765 inches

**Bushing Length:**

Between 0.455 inches and 0.485 inches

**Body Length:**

Between 1.295 inches and 1.325 inches

**Body Width:**

Between 0.735 inches and 0.765 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.237 inches and 0.243 inches

**Actuator Height:**

Between 0.675 inches and 0.705 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

125.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, single throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

4 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0