## NSN 5930-00-690-5504



View Online at https://aerobasegroup.com/nsn/5930-00-690-5504

## Push Switch - Page 1 of 2 **Thread Class:** 2a **Body Style:** Bushing mounted Hazardous Locations/environmental Protection: Moisture proof **Body Diameter:** 0.562 inches **Bushing Length:** 0.312 inches **Body Length:** 0.422 inches **Actuator Diameter:** 0.375 inches **Actuator Height:** 0.250 inches Maximum Voltage Rating In Volts: 120.0 ac and 38.0 dc Inclosure Type: Fully enclosed **Mounting Method:** Threaded bushing **Features Provided:** Actuator seal Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.500 inches **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally closed, double break, momentary action, with contact on arm. Single switch unit Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive dc **Thread Series Designator:** Un **Terminal Type And Quantity:** 1 tab, solder lug and 2 screw Shelf Life:

N/a

Unit Of Measure:

---

## **Demilitarization:**

No

## NSN 5930-00-690-5504

Push Switch - Page 2 of 2

Fiig: A053a0

