

View Online at <https://aerobasegroup.com/nsn/5930-00-691-1279>

**Thread Class:**

2b single pressure connection

**Inside Diameter:**

0.438 inches single connection

**Hazardous Locations/environmental Protection:**

Dustproof and watertight

**Overall Length:**

5.750 inches

**Overall Height:**

10.938 inches

**Overall Width:**

3.000 inches

**Body Length:**

5.750 inches

**Body Height:**

10.688 inches

**Unthreaded Mounting Hole Diameter:**

0.375 inches

**Longest Horizontal Distance Between Mounting Centers:**

3.000 inches

**Shortest Horizontal Distance Between Mounting Centers:**

1.016 inches

**Longest Vertical Distance Between Mounting Centers:**

4.250 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Electrical access port

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

5000.00 pounds per square inch

**Thread Size:**

0.438 inches single pressure connection

**Mounting Facility Pattern:**

Isosceles triangle

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

9.6 amperes inductive load third voltage

**Contact Adjustability:**

Actuation point adjustable

**Contact Adjustment Range:**

+500.00/+5000.00 actuation point pounds per square inch

**Contact Adjustment Type:**

External actuation point screw

**Contact Voltage Rating In Volts:**

550.0 dc at sea level fourth voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Media For Which Designed:**

Gas or liquid

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Rectangular

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0