

View Online at <https://aerobasegroup.com/nsn/5930-00-691-1279>

Thread Class:

2b single pressure connection

Inside Diameter:

0.438 inches single connection

Hazardous Locations/environmental Protection:

Dustproof and watertight

Overall Length:

5.750 inches

Overall Height:

10.938 inches

Overall Width:

3.000 inches

Body Length:

5.750 inches

Body Height:

10.688 inches

Unthreaded Mounting Hole Diameter:

0.375 inches

Longest Horizontal Distance Between Mounting Centers:

3.000 inches

Shortest Horizontal Distance Between Mounting Centers:

1.016 inches

Longest Vertical Distance Between Mounting Centers:

4.250 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Proof Pressure:

5000.00 pounds per square inch

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

9.6 amperes inductive load third voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+500.00/+5000.00 actuation point pounds per square inch

Contact Adjustment Type:

External actuation point screw

Contact Voltage Rating In Volts:

550.0 dc at sea level fourth voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Rectangular

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0