

View Online at <https://aerobasegroup.com/nsn/5930-00-693-3504>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Corrosion resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.781 inches

Body Length:

2.250 inches

Body Width:

0.859 inches

Body Height:

1.250 inches

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

0.188 inches

Actuator Style:

Round

Actuator Diameter:

0.375 inches

Actuator Height:

0.219 inches

Actuator Free Position Height:

0.906 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, double make, momentary action single switch unit

Switch Release Force:

28.0 ounces

Switch Actuating Force:

45.0 ounces

Actuator Movement:

Between 0.100 pretravel inches and 0.150 pretravel inches and 0.219 overtravel inches and 0.015 differential inches and 0.035 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 7.500 amperes inductive dc and 7.500 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes lamp ac

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0