

View Online at <https://aerobasegroup.com/nsn/5930-00-693-3504>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.781 inches

**Body Length:**

2.250 inches

**Body Width:**

0.859 inches

**Body Height:**

1.250 inches

**Case Material:**

Metal

**Unthreaded Mounting Hole Diameter:**

0.188 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.375 inches

**Actuator Height:**

0.219 inches

**Actuator Free Position Height:**

0.906 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, double make, momentary action single switch unit

**Switch Release Force:**

28.0 ounces

**Switch Actuating Force:**

45.0 ounces

**Actuator Movement:**

Between 0.100 pretravel inches and 0.150 pretravel inches and 0.219 overtravel inches and 0.015 differential inches and 0.035 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive dc and 7.500 amperes inductive dc and 7.500 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes lamp ac

**Terminal Type And Quantity:**

2 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0