## NSN 5930-00-694-9553

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-694-9553

9
Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Fungus proof and moisture proof and watertight
Overall Length:
5.312 inches
Overall Height:
2.562 inches
Overall Width:
3.250 inches
Case Material:
Metal
Actuator Style:
Round
Actuator Free Position Height:
0.656 inches
Housing Height:
2.562 inches
Housing Length:
5.312 inches
Housing Width:
3.250 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.438 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
2.812 inches
Maximum Voltage Rating In Volts:
440.0 ac and 230.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 pole, double throw, double break/double make, one position momentary single switch unit
Switch Release Force:
20.0 ounces
Switch Actuating Force:
228.0 ounces
Actuator Movement:
16.0 pretravel degrees and 6.0 overtravel degrees and 12.0 differential degrees
Contact Load Current Rating At Maximum Rated Voltage:

Terminal Type And Quantity:

5.000 amperes resistive dc and 5.000 amperes resistive ac

3 screw

## NSN 5930-00-694-9553

Sensitive Switch - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0